

optional
LTE / GNSS / Wi-Fi



2x USB 2.0
microSD
DisplayPort

Image similar

Power Supply
9 ... 45VDC

CAN

2x GBit LAN

USB 3.1

HDMI

IPC/COMPACT A3N - RS

This fanless COMPACT A3N generation is based on the NVIDIA Jetson Xavier NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding mobile AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- Passively cooled, no moving parts
- Long term availability with fixed BOM

 **NVIDIA.** Linux for Tegra (L4T)

Product Highlights

Maintenance free
Power Ignition Controller
Shock and vibration resistant
LTE, GNSS and Wi-Fi connectivity options
No moving parts / passively cooled

Product Features

384-core NVIDIA Volta™ GPU
with 48 Tensor Cores
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU
8GB 128-bit LPDDR4x RAM soldered on board
M.2 NVMe slot for storage expansion up to 2TB
USB 3.0 and HDMI 2.0 ports with dust covers
Ethernet, passive or active CAN
LTE, GNSS & WiFi
Aluminum & Stainless steel housing
Protection class IP65

Industries / Applications

Automated Guided Vehicles (AGV)
Automotive
Transportation
Robotics
Agriculture
Construction Vehicles



Processor module / Performance		
NVIDIA Jetson Xavier NX 384-core NVIDIA Volta™ GPU with 48 Tensor Cores	•	•
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU	•	•
AI Performance (INT8)	21 TOPs	21 TOPs
Memory / Storage		
Data Cache Size	2MB	2MB
128-bit LPDDR4x RAM soldered on board	8GB	8GB
eMMC 5.1 Flash Storage on board	16GB	16GB
M.2 2280 NVMe SSD socket ⁵	1	1
microSD card socket ²	1	1
Features		
Inertial measurement unit (IMU) STMicroelectronics ISM330DHCXTR	•	•
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Hardware Watchdog & Temperature supervisor	•	•
Communication Interfaces		
Graphic interface <small>behind the service cover</small>		DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small>	(micro USB Type AB)	1
USB version 2.0 <small>behind the service cover</small>	(Type A)	2
Graphic interface		HDMI 2.0
USB version 3.1	(Type A)	1
USB version 2.0 ¹	(Type A)	optional
Ethernet 10/100/1000Mbit (1x native, 1x I210-IT)	(M12 female, x-coded)	2
Active/passive-CAN ESD protected, isolated	(M12 female, a-coded)	1
Serial RS232 ²		2
Mini PCIe socket ²		2
I2C bus ²		1
Buzzer		1
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface ¹		on request
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface ¹		on request
Wireless Connectivity		
Cellular Module (LTE/UMTS/GSM) with GNSS positioning functionality Sierra Wireless MC7455 - M2M only! (Dual nano SIM)		3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 4.1 SparkLAN WPEB-263ACNI(BT)		2x RP-SMA
High precision GNSS module ¹ u-blox ZED-F9P module		optional
Technical Data		
Dimensions [mm] (housing, excl. mounting)		w182 x h60 x d127
Dimensions [mm] (housing, incl. mounting)		w218 x h60 x d127
Net weight [gram]		~ 1400
Non isolated input voltage, with ignition controller, reverse polarity protected	(M12 male, a-coded)	9... 45VDC
Current consumption typ. in mA @ 24V without Add-Ins, idle		~ 400
Power consumption typ. in Watt @ 24V without Add-Ins, idle		~ 10
Environmental Conditions		
Operating temperature ³		-25°C ... +65°C
Storage temperature		-25°C ... +85°C
Ingress protection standard according to EN60529		IP65
Conformal coating ⁴		on request
Shock (designed to meet)		EN60068-2-27
Vibration (designed to meet)		EN60068-2-64
EMI-Conformity (designed to meet)		EN55032 / EN55035
Safety (designed to meet)		EN62368-1
Radio and Telecommunication (designed to meet)		RED
MTBF @ 25°C ambient <small>excluding battery</small>		tbd

¹ Please contact factory for minimum order quantities² Internal connector³ Depending on installation situation and interface connection. Please see user documentation⁴ On all possible components (excl. Xavier NX module, connectors and wireless devices)⁵ It is possible to equip the products with a Cactus Technologies 270P Series NVMe SSD from the factory, use these part codes:

IPC/RSA3NI19-[E/F]102S-01 = 128GB | IPC/RSA3NI19-[E/F]102S-02 = 256GB | IPC/RSA3NI19-[E/F]102S-05 = 512GB | IPC/RSA3NI19-[E/F]102S-10 = 1TB

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2021 Syslogik Datentechnik AG
All rights reservedSyslogik Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 0.5 | May 2021

For further information and support:
info@syslogik.com
support@syslogik.com
www.syslogik.com+41 56 200 90 40
+49 7741 9671-420Switzerland (Headquarters)
Germany and Austria

syslogik
industrial computing