

## COMPACT AI Vehicle Series

Computer Vision Edge Unit with NVIDIA Jetson Xavier NX

optional  
LTE / GNSS / Wi-Fi



2x USB 2.0  
microSD  
DisplayPort

Image similar

Power Supply  
9 ... 45VDC

CAN

2x GBit LAN

USB 3.1

HDMI

## IPC/COMPACT A3N - RS

This fanless COMPACT A3N generation is based on the NVIDIA Jetson Xavier NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding mobile AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- Passively cooled, no moving parts
- Long term availability with fixed BOM

 **NVIDIA.** Linux for Tegra (L4T)

### Product Highlights

Maintenance free  
Power Ignition Controller  
Shock and vibration resistant  
LTE, GNSS and Wi-Fi connectivity options  
No moving parts / passively cooled

### Product Features

384-core NVIDIA Volta™ GPU  
with 48 Tensor Cores  
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU  
8GB / 16GB 128-bit LPDDR4x RAM  
M.2 NVMe slot for storage expansion up to 2TB  
USB 3.1 and HDMI 2.0 ports with dust covers  
Ethernet, passive or active CAN  
LTE, GNSS & WiFi  
Aluminum & Stainless steel housing  
Protection class IP65

### Industries / Applications

Autonomous Mobile Robots (AMRs)  
Automotive  
Transportation  
Robotics  
Agriculture  
Construction Vehicles

Processor module / Performance		
NVIDIA Jetson Xavier NX   384-core NVIDIA Volta™ GPU with 48 Tensor Cores	•	•
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU		
NVIDIA Jetson Xavier NX (16GB RAM)   384-core NVIDIA Volta™ GPU with 48 Tensor Cores	optional	optional
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU		
AI Performance (INT8)	21 TOPs	21 TOPs
Memory / Storage		
Data Cache Size	2MB	2MB
128-bit LPDDR4x RAM soldered on board	8GB	8GB
eMMC 5.1 Flash Storage on board	16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) <sup>5</sup>	1	1
microSD card socket <sup>2</sup>	1	1
Features		
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Inertial measurement unit (IMU) <sup>1</sup> STMicroelectronics ISM330DHCXTR	on request	on request
Communication Interfaces		
Display output <small>behind the service cover</small>	DisplayPort 1.4	DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small>	(micro USB Type AB)	1
USB version 2.0 <small>behind the service cover</small>	(Type A)	2
Display output	HDMI 2.0	HDMI 2.0
USB version 3.1 (5 Gbit/s)	(Type A)	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT)	(M12 female, x-coded)	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated	(M12 female, a-coded)	1
Mini PCIe socket <sup>2</sup> , used for extensions depending on configuration		2
Serial RS232 <sup>1</sup>	(M12 female, a-coded)	optional
USB version 2.0 <sup>1</sup>	(M12 female, a-coded)	optional
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>		on request
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>		on request
Wireless Connectivity		
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS <sup>6</sup> Telit LE910C4-WWX (Dual nano SIM support)	none	3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.0 <sup>6</sup> Enwicon WXM6218	none	2x RP-SMA
High precision GNSS module <sup>1</sup> u-blox ZED-F9R / F9P	on request	on request
Technical Data		
Dimensions [mm] (housing, excl. mounting)	w182 x h60 x d127	w182 x h60 x d127
Dimensions [mm] (housing, incl. mounting)	w218 x h60 x d127	w218 x h60 x d127
Net weight [gram]	~ 1600	~ 1650
Non isolated input voltage, with ignition controller, reverse polarity protected	(M12 male, a-coded)	9... 45VDC
Power consumption typ. in Watt @ 24V without Add-Ins, idle		~ 8.5
Environmental Conditions		
Operating temperature <sup>3</sup>	-25°C ... +70°C	-25°C ... +70°C
Storage temperature	-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529	IP65	IP65
Conformal coating <sup>4</sup>	on request	on request
Shock (designed to meet)	EN60068-2-27	EN60068-2-27
Vibration (designed to meet)	EN60068-2-64	EN60068-2-64
EMC-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	n/a	RED
MTBF @ 25°C ambient <small>according to Telcordia SR-332, Environment GB, excluding battery and SSD</small>	~ 530 000h	~ 375 000h

<sup>1</sup> Please contact factory for minimum order quantities<sup>2</sup> Internal connector<sup>3</sup> Depending on installation situation and interface connection. Please see user documentation.<sup>4</sup> On all possible components (excl. Xavier NX module, connectors and wireless devices)<sup>5</sup> It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes:

IPC/RSA3NI19-[E/F]102S-01 = 120GB | IPC/RSA3NI19-[E/F]102S-02 = 240GB | IPC/RSA3NI19-[E/F]102S-05 = 480GB | IPC/RSA3NI19-[E/F]102S-10 = 960GB

<sup>6</sup> On products version 2.0 and up, these LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL.

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogik Datentechnik AG  
All rights reservedSyslogik Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:  
info@syslogik.com  
support@syslogik.com  
www.syslogik.com+41 56 200 90 40  
+49 7741 9671-420Switzerland (Headquarters)  
Germany and Austria

**syslogik**  
industrial computing