

COMPACT AI Rugged Series

Intelligent Machine Learning Unit with NVIDIA Jetson TX2 NX

optional
LTE / GNSS / Wi-Fi



2x USB 2.0
microSD
DisplayPort

Image similar

Power Supply
9 ... 45VDC

CAN

2x Gbit LAN

USB 3.1

HDMI

RPC/COMPACT A2N

This fanless COMPACT A2N generation is based on the NVIDIA Jetson TX2 NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- IP67 protection
- Product lifecycle management
- Long term availability with fixed BOM



NVIDIA. Linux for Tegra (L4T)

Product Highlights

Ultra rugged
Sealed housing, protection class IP67
Maintenance free
Power Ignition controller
No moving parts / passively cooled
Pressure equalization membrane
Resistance to chemicals
Long term availability (fixed BOM)

Product Features

256-core NVIDIA Pascal™ GPU Dual-Core
NVIDIA Denver 2 64-Bit CPU Quad-Core
ARM® Cortex®-A57 MPCore
4GB 128-bit LPDDR4x RAM soldered on board
M.2 NVMe slot for storage expansion up to 2TB
Ethernet, USB, active / passive CAN
Optional LTE & WiFi extensions
Aluminum housing
Ingress Protection class IP67

Markets / Applications

Autonomous Mobile Robots (AMRs)
Agriculture
Construction
Transportation
Off-Highway Vehicles
Heavy Industry
Outdoor applications



Processor module / Performance		
NVIDIA Jetson TX2 NX 256-core NVIDIA Pascal™ GPU	•	•
6-Core ARM CPU (Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore)	•	•
AI Performance	1.33 TFLOPs	1.33 TFLOPs
Memory / Storage		
Data Cache Size	2MB	2MB
128-bit LPDDR4 RAM soldered on board	4GB	4GB
eMMC 5.1 Flash Storage on board	16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) ⁵	1	1
microSD card socket ²	1	1
Features		
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Hardware Watchdog & Temperature supervisor	•	•
Inertial measurement unit (IMU) ¹ STMicroelectronics ISM330DHCXTR	optional	optional
Buzzer	optional	optional
Communication Interfaces		
Video output <small>behind the service cover</small>	DisplayPort 1.4	DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small> (micro USB Type AB)	1	1
USB version 2.0 <small>behind the service cover</small> (Type A)	2	2
Video output	HDMI 2.0	HDMI 2.0
USB version 3.1 (5 Gbit/s) (Type A)	1	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT) (M12 female, x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (M12 female, a-coded)	1	1
Mini PCIe socket ²	2	2
I2C bus ²	1	1
Serial RS232 ¹ (M12 female, a-coded)	optional	optional
USB version 2.0 ¹ (M12 female, a-coded)	optional	optional
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface ¹	on request	on request
Wireless Connectivity		
Cellular Module (LTE/UMTS/GSM) with GNSS positioning functionality Sierra Wireless MC7455 - M2M only! (Dual nano SIM)	none	3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 4.1 SparkLAN WPEB-263ACNI(BT)	none	2x RP-SMA
High precision GNSS module ¹ u-blox ZED-F9P module	optional	optional
Technical Data		
Dimensions [mm] (housing, incl. mounting)	w245 x h66 x d165	w245 x h66 x d165
Net weight [gram]	~2300	~2350
Non isolated Input voltage, with Ignition controller, reverse polarity protected (M12 male, a-coded)	9 ... 45VDC	9 ... 45VDC
Idle power consumption typ. in Watt @ 24V without Add-Ins	~8.5	~8.5
Environmental Conditions		
Operating temperature ³	-25°C ... +70°C	-25°C ... +70°C
Storage temperature	-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529	IP67	IP67
Conformal coating ⁴	on request	on request
Shock (designed to meet)	EN60068-2-27	EN60068-2-27
Vibration (designed to meet)	EN60068-2-64	EN60068-2-64
EMI-Conformity (designed to meet)	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	n/a	RED
estimated MTBF @ 25°C ambient <small>excluding battery</small>	~550 000h	~385 000h

¹ Please contact factory for minimum order quantities

² Internal connector

³ Depending on installation situation and interface connection. Derating of max. operating temp. is possible when using the cellular LTE module. Please see user documentation.

⁴ On all possible components (excl. TX2 NX module, connectors and wireless devices)

⁵ It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes: RPC/RSA2NH20-[A/B]102S-01 = 120GB | RPC/RSA2NH20-[A/B]102S-02 = 240GB | RPC/RSA2NH20-[A/B]102S-05 = 480GB | RPC/RSA2NH20-[A/B]102S-10 = 960GB

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2022 Syslogic Datentechnik AG
All rights reserved

Syslogic Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 1.1 | October 2022

For further information and support:
info@syslogic.com
support@syslogic.com
www.syslogic.com

+41 56 200 90 40
+49 7741 9671-420

Switzerland (Headquarters)
Germany and Austria

 **syslogic**
industrial computing