

## COMPACT AI Rugged Series

Computer Vision Edge Unit with NVIDIA Jetson TX2 NX

LTE / GNSS / Wi-Fi



2x USB 2.0  
microSD  
DisplayPort

Image similar

Power Supply  
9 ... 45VDC

CAN

2x Gbit LAN

USB 3.1

HDMI

## RPC/COMPACT A2N

This fanless COMPACT A2N generation is based on the NVIDIA Jetson TX2 NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- IP67 protection
- Product lifecycle management
- Long term availability with fixed BOM



**NVIDIA.** Linux for Tegra (L4T)

### Product Highlights

Ultra rugged  
Sealed housing, protection class IP67  
Maintenance free  
Power Ignition controller  
No moving parts / passively cooled  
Pressure equalization membrane  
Resistance to chemicals  
Long term availability (fixed BOM)

### Product Features

256-core NVIDIA Pascal™ GPU Dual-Core  
NVIDIA Denver 2 64-Bit CPU Quad-Core  
ARM® Cortex®-A57 MPCore  
4GB 128-bit LPDDR4x RAM soldered on board  
M.2 NVMe slot for storage expansion up to 2TB  
Ethernet, USB, active / passive CAN  
Optional LTE & WiFi extensions  
Aluminum housing

### Markets / Applications

Autonomous Mobile Robots (AMRs)  
Agriculture  
Construction  
Transportation  
Off-Highway Vehicles  
Heavy Industry  
Outdoor applications



**Processor module / Performance**

NVIDIA Jetson TX2 NX   256-core NVIDIA Pascal™ GPU	•
6-Core ARM CPU (Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore)	•
AI Performance	1.33 TFLOPs

**Memory / Storage**

Data Cache Size	2MB
128-bit LPDDR4 RAM soldered on board	4GB
eMMC 5.1 Flash Storage on board	16GB
M.2 2280 Key M socket (for NVMe SSD) <sup>5</sup>	1
microSD card socket <sup>2</sup>	1

**Features**

Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•
Hardware Watchdog & Temperature supervisor	•
Inertial measurement unit (IMU) <sup>1</sup> STMicroelectronics ISM330DHCXTR	on request
Buzzer	on request

**Communication Interfaces**

Video output <small>behind the service cover</small>		DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small>	(micro USB Type AB)	1
USB version 2.0 <small>behind the service cover</small>	(Type A)	2
Video output		HDMI 2.0
USB version 3.1 (5 Gbit/s)	(Type A)	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT)	(M12 female, x-coded)	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated	(M12 female, a-coded)	1
Mini PCIe socket <sup>2</sup>		2
I2C bus <sup>2</sup>		1
Serial RS232 <sup>1</sup>	(M12 female, a-coded)	on request
USB version 2.0 <sup>1</sup>	(M12 female, a-coded)	on request
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>		on request

**Wireless Connectivity**

Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS	none
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth	none
High precision GNSS module <sup>1</sup> u-blox ZED-F9R / F9P	none

**Technical Data**

Dimensions [mm] (housing, incl. mounting)		w245 x h66 x d165
Net weight [gram]		~2300
Non isolated Input voltage, with Ignition controller, reverse polarity protected	(M12 male, a-coded)	9 ... 45VDC
Idle power consumption typ. in Watt @ 24V without Add-Ins		~8.5

**Environmental Conditions**

Operating temperature <sup>3</sup>		-25°C ... +70°C
Storage temperature		-25°C ... +85°C
Ingress protection standard according to EN60529		IP67
Conformal coating <sup>4</sup>		on request
Shock (designed to meet)		EN60068-2-27
Vibration (designed to meet)		EN60068-2-64
EMI-Conformity (designed to meet)		EN55032 / EN55035
Safety (designed to meet)		EN62368-1
Radio and Telecommunication (designed to meet)		n/a
estimated MTBF @ 25°C ambient <small>excluding battery</small>		~550 000h

<sup>1</sup> Please contact factory for minimum order quantities<sup>2</sup> Internal connector<sup>3</sup> Depending on installation situation and interface connection. Derating of max. operating temp. is possible when using the cellular LTE module. Please see user documentation.<sup>4</sup> On all possible components (excl. TX2 NX module, connectors and wireless devices)<sup>5</sup> It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes:

RPC/RSA2NH20-[A/B]102S-01 = 120GB | RPC/RSA2NH20-[A/B]102S-02 = 240GB | RPC/RSA2NH20-[A/B]102S-05 = 480GB | RPC/RSA2NH20-[A/B]102S-10 = 960GB

<sup>6</sup> On products version 2.0 and up, these LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL.

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG  
All rights reserved

Syslogic Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:  
info@syslogic.com  
support@syslogic.com  
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)  
+49 7741 9671-420 Germany and Austria

 **syslogic**  
industrial computing